





F9 Optical Distribution Frame - 84 Tray



Right Hand Cassette



Premium Cable Management



## Overview

The **F9 Optical Distribution Frame** is a high-density, modular platform designed for efficient fibre splicing, termination, and patching. Its compact 300 mm depth and front-access architecture enable seamless installation in space-constrained environments, including wall-mounted, back-to-back, and end-of-row configurations.

Supporting up to 96 SpliceGroup™ cassettes, the F9 provides scalable capacity with integrated cable management and a patching area for clean routing between cassettes and network applications. The system is compatible with all SpliceGroup right-handed cassette types—Splice, Patch, and Passive Optical Devices and accommodates diverse cable formats with both top and bottom entry options.

Standard patch-cord lengths minimise cabling complexity and simplify inventory control. With support for up to 2,208 fibre connections using Small Form Factor (SFF) connectors, the F9 is engineered for rapid deployment, high-density fibre management, and future-ready scalability.

## Main Features

- Modular, customisable design with capacity for up to 96 cassettes
- Supports up to 2208 fibre connections
- Clear routing paths for simplified fibre identification and tracing
- Standard patch cord lengths to streamline stock management
- Compatible with all SpliceGroup™ cassette types (Splice, Ribbon, Patch, Passive)
- High-density cable distribution with multiple breakout options
- Top and bottom cable entry configuration
- Front access supports wall-mounted deployment, optimising space usage
- Suitable for cross-connect or point to point architectures.

**Specifications**

**General Specifications**

Application	Data Centre, Co-Location, Enterprise, FTTX
Product Type	Optical Distribution Frame (ODF)
Cassette Option	All
Compatibility	Conventional Cable, Ribbon, F-tube, Blown Fibre, Plug & Play

**Mechanical Characteristics**

Dimensions (HxWxD)	2200mm x 900mm x 300mm (86.61 in x 35.43 in x 11.81 in)
Weight (Approximately)	152 kg (335.10 lb)

**Material**

Frame	Aluminium
Doors and Panel	Steel

**Colour**

Side Doors and Panels	Light Grey (RAL 7035)
	Jet Black (RAL 9005)

**ODF Options**

Cable Entry & Exit	Top and Bottom
Frame Colour Available	Grey and Black

**Dimension & Images**

